



ZESTAWIENIE KOŚCI

pulsar cams					comet cams				flexor cams				20 21
SIZE	CODE	RANGE min/max	WEIGHT	STRENGTH	CODE	RANGE min/max	WEIGHT	STRENGTH	CODE	RANGE min/max	WEIGHT	STRENGTH	SIZE
0.25	-	-	-	-	31005.1	12-16,5 mm/ 0,47-0,63 in	65g/ 2,29 oz.	7 kN	31008.1	12-16 mm/ 0,47-0,63 in	76g/ 2,68 oz.	7 kN	0.25
0.5	-	-	-	-	31005.2	14-20 mm/ 0,55-0,79 in	70g/ 2,47 oz.	9 kN	31008.2	14-20 mm/ 0,55-0,79 in	81g/ 2,86 oz.	9 kN	0.5
0.7	-	-	-	-	31005.3	17-24,5 mm/ 0,67-0,94 in	72g/ 2,54 oz.	10 kN	31008.3	16-22 mm/ 0,63-0,87 in	84g/ 2,96 oz.	10 kN	0.7
1	31006.1	19-30 mm/ 0,75-1,18 in	105g/ 3,70 oz.	14 kN	31005.4	20-29 mm/ 0,79-1,14 in	89g/ 3,14 oz.	11 kN	31008.4	19-27 mm/ 0,75-1,06 in	97g/ 3,42 oz.	11 kN	1
2	31006.2	25-40 mm/ 0,98-1,57 in	114g/ 4,06 oz.	14 kN	31005.5	27-41 mm/ 1,06-1,61 in	97g/ 3,42 oz.	11 kN	31008.5	22-33 mm/ 0,87-1,30 in	106g/ 3,74 oz.	11 kN	2
3	31006.3	35-53 mm/ 1,38-2,09 in	153g/ 5,40 oz.	14 kN	31005.6	35-53 mm/ 1,38-2,08 in	131g/ 4,62 oz.	12 kN	31008.6	27-43 mm/ 1,06-1,69 in	115g/ 4,06 oz.	11 kN	3
4	31006.4	44-77 mm/ 1,73-2,72 in	174g/ 6,14 oz.	12 kN	31005.7	48-67 mm/ 1,89-2,64 in	155g/ 5,47 oz.	12 kN	31008.7	33-53 mm/ 1,30-2,10 in	151g/ 5,33 oz.	12 kN	4
5	31006.5	58-90 mm/ 2,28-3,62 in	214g/ 7,55 oz.	12 kN	31005.8	61-91 mm/ 2,4-3,58 in	220g/ 7,76 oz.	12 kN	31008.8	43-67 mm/ 1,69-2,64 in	168g/ 5,93 oz.	12 kN	5
6	31006.6	73-118 mm/ 2,87-4,65 in	258g/ 9,10 oz.	12 kN	31005.9	72-113 mm/ 2,84-4,45 in	250g/ 8,82 oz.	12 kN	31008.9	55-85 mm/ 2,17-3,35 in	223g/ 7,87 oz.	12 kN	6
7	31006.7	99-146 mm/ 3,9-5,75 in	322g/ 11,36 oz.	12 kN	31005.10	90-140 mm/ 3,54-5,51 in	310g/ 10,93 oz.	12 kN	31008.10	70-105 mm/ 2,76-4,13 in	275g/ 9,70 oz.	12 kN	7